

Product Technical Data Sheet



Grade : N774

Product Description

It is a semi reinforcing black with a low surface area and structure but it's structure is slightly higher than N772.

Effect on Compound Properties

- It is used in applications requiring minimal hysteresis and reinforcement that provides excellent processibility.

Applications

- It is used in innerliners of tires and numerous mechanical rubber goods.

Technical Specifications

	Test Method	Units	Typical Target
Iodine Adsorption No.	D-1510	(g/kg)	29.0
NSA Multipoint	D-6556	(m ² /g)	30.0
STSA	D-6556	m ² /g)	29.0
Oil Absorption No.	D-2414	(cc/100 g)	72.0
Compressed Oil Absorption No.	D-3493	(cc/100g)	63.0

Packaging

- 25 kgs paper bag
- 875 - 1200 kgs big bag

Contact Information

2nd Floor, Ruby House, 8, India Exchange Place, Kolkata – 700001, India
+91 33 2230 9953/ 2230 4363

Disclaimer

This information is provided as a convenience and for informational purposes only. No guarantee or warranty as to this information, or any product to which it relates, is given or implied. This information may contain inaccuracies, errors or omissions and Himadri Speciality Chemical Ltd. disclaims all warranties express or implied, including merchantability or fitness for a particular purpose as to (i) such information, (ii) any product or (iii) intellectual property infringement. In no event is Himadri Speciality Chemical Ltd. responsible for, and does not accept and hereby disclaims liability for, any damages whatsoever in connection with the use of or reliance on this information or any product to which it relates.